

## How to measure a replacement door

M&L doors are made to exact millimetre sizes, or within 1/16". To ensure a replacement door fits correctly please take measurements as follows:

**Width** – measure the exact width of the opening in the frame within which the door is to be fitted. If it's an old building and varies, measure the widest point. Deduct 3mm (1/8") from the measurement.

**Height** – measure the exact height of the opening in frame within which the door is to be fitted, allowing for uneven floors carpets, etc. Measure the greatest point. And deduct 6mm (1/4").

**Thickness** – doors are made 44mm (1 3/4") or 57mm (2 1/4") depending on the frame rebate (recess within which the door is fitted), preference, and whether it is double-glazed (which always requires 57mm). Both thicknesses are strong enough for all normal domestic use.

**Left or right hung, double doors** – These are supplied with the two doors rebated together so they 'overlap' and one door opens before the other. As standard they are made with the right-hand door opening first when viewed from the hinge side; that is viewed from the side into which the door opens. Please say when ordering if you would want the left-hand door to open first.



Shoreditch door in 18th-C frame with original hinges

### ORDERING

Please send your requirements with dimensions to [doors@marstonmail.com](mailto:doors@marstonmail.com) and we will promptly reply with a price. Or buy our standard sizes [online](#).

